FT2306V-FFP2

Respirator

The masks offer half-face coverage with 2 headband style straps for a secure fit. The cupped design offers low breathing resistance and is ergonomically designed for comfort.



MATERIALOF BODY PART

4 Ply Nonwoven

Outer layer: 30g PP+ 100g needle-punched fabric Middle layer: 25g double layers melt blown fabric Inner layer: 160g needle-punched fabric

MATERIAL OF NOSE CLIP

Adjustable AluminumBraided

MATERIAL OF HEAD ON STRIP

Spandex elastic

SPONGE BAR

Polyurethane (PU) foam

SIZE

One size

BREARHING VALVE DEVICE

Yes

PRODUCTION METHOD

Ultrasonic welded

REUSABLE

No

STYLE

Cup shape mask with Valve

PACKAGE

15 PCS/B0X 300PCS/CTN

Carton dimension: 69*28.5*46.5CM

Net weight: 4. 8KG Gross weight: 7. 2KG

















Safety masks meettheEuropean standardEN149:2001+A1:2009 FFP2 standard requirements







Product parameters

Inspiratory resistance(30LPM±1LPM):≤7MMH2O

Inspiratory resistance(95LPM±1LPM):≤24MMH2O

Filtration efficiency(salt spray 1%):≥94%

Filtration efficiency(paraffin oil or DOP 1%):≥94%

Headband tension:20N/10s

Product features

- CE FFP2 CERTIFIED: FFP2 masks remove at least 94% of non -oilbased particles down to 0.3 microns.
- COMFORTABLE & ADJUSTABLE: High quality, light weight construction provides comfort, while the adjustable nose clip with foam and heavy duty straps conforms to your facial features for an enhanced seal.
- BREATHE EASY:Built-in exhalation cool valve reduces heat, moisture, and humidity build-up, to keep you more comfortable longer
- Common Uses:Prevents particulate matter from the processing of minerals, coal, iron ore, flour, etc.



Scan to learn about protecting planet information

Ningbo Fastest Safety Protection Products Co., Ltd.

Rm. 1801 Jiamei Buliding, No.746 Taikang Zhong Rd., Yinzhou District, Ningbo China, 31 5199 TEL: +86-574-82822581 FAX: +86-574-82822578 EMAIL: ft@ftsafety.cn Website: www.ftsafety.com