

# FT2306-FFP2

## Respirator



The masks offer half-face coverage with 2 headband style straps for a secure fit. The cupped design offers low breathing resistance and is ergonomically designed for comfort.

| Descriptions                                                                       |
|------------------------------------------------------------------------------------|
| <b>MATERIALOF BODY PART</b>                                                        |
| 4 Ply Nonwoven                                                                     |
| Outer layer: 30g PP+100g needle-punched fabric                                     |
| Middle layer: 25g double layers melt blown fabric                                  |
| Inner layer: 160g needle-punched fabric                                            |
| <b>MATERIAL OF NOSE CLIP</b>                                                       |
| Adjustable AluminumBraided                                                         |
| <b>MATERIAL OF HEAD ON STRIP</b>                                                   |
| Spandex elastic                                                                    |
| <b>SPONGE BAR</b>                                                                  |
| Polyurethane (PU) foam                                                             |
| <b>SIZE</b>                                                                        |
| One size                                                                           |
| <b>BREARHING VALVE DEVICE</b>                                                      |
| No                                                                                 |
| <b>PRODUCTION METHOD</b>                                                           |
| Ultrasonic welded                                                                  |
| <b>REUSABLE</b>                                                                    |
| No                                                                                 |
| <b>STYLE</b>                                                                       |
| Cup shape mask                                                                     |
| <b>PACKAGE</b>                                                                     |
| 20 PCS/BOX                                                                         |
| 400PCS/CTN                                                                         |
| Carton dimension: 69*28.5*46.5CM                                                   |
| Net weight: 4.1KG                                                                  |
| Gross weight:6.5KG                                                                 |
|                                                                                    |
| <b>Certification</b>                                                               |
| Safety masks meettheEuropean standardEN149:2001+A1:2009 FFP2 standard requirements |



| Product parameters                                 |
|----------------------------------------------------|
| Inspiratory resistance(30LPM±1LPM):≤7MMH2O         |
| Inspiratory resistance(95LPM±1LPM):≤24MMH2O        |
| Filtration efficiency(salt spray 1%):≥94%          |
| Filtration efficiency(paraffin oil or DOP 1%):≥94% |
| Headband tension:20N/10s                           |

### Product features

- CE FFP2 CERTIFIED: FFP2 masks remove at least 94% of non -oil-based particles down to 0.3 microns.
- COMFORTABLE & ADJUSTABLE:High quality, light weight construction provides comfort, while the adjustable nose clip with foam and heavy duty straps conforms to your facial features for an enhanced seal.
- BREATHE EASY:Built-in exhalation cool valve reduces heat, moisture, and humidity build-up, to keep you more comfortable longer
- Common Uses:Prevents particulate matter from the processing of minerals, coal, iron ore, flour, etc.



waste  
reducing  
product life



Scan to  
learn about  
protecting planet  
information



### Ningbo Fastest Safety Protection Products Co.,Ltd.

Rm. 1801 Jiamei Buliding, No.746 Taikang Zhong Rd., Yinzhou District,Ningbo China,31 5199  
TEL: +86-574-82822581 FAX: +86-574-82822578 EMAIL: ft@ftsafety.cn  
Website: www.ftsafety.com