

# FT2302V-FFP2

## Respirator



The masks offer half-face coverage with 2 headband style straps for a secure fit. The cupped design offers low breathing resistance and is ergonomically designed for comfort.

Descriptions
<b>MATERIAL OF BODY PART</b>
4 Ply Nonwoven Outer layer: 30g PP+100g needle-punched fabric Middle layer: 25g double layers melt blown fabric Inner layer: 160g needle-punched fabric
<b>MATERIAL OF NOSE CLIP</b>
Adjustable Aluminum Braided
<b>MATERIAL OF HEAD ON STRIP</b>
Spandex elastic
<b>SPONGE BAR</b>
Polyurethane (PU) foam
<b>SIZE</b>
One size
<b>BREATHING VALVE DEVICE</b>
Yes
<b>PRODUCTION METHOD</b>
Ultrasonic welded
<b>REUSABLE</b>
No
<b>STYLE</b>
Cup shape mask with Valve
<b>PACKAGE</b>
15 PCS/BOX 300PCS/CTN Carton dimension: 64*31.5*43.5CM Net weight: 4.5KG Gross weight: 6.9KG
<b>Certification</b>

Safety masks meet the European standard EN149:2001+A1:2009 FFP2 standard requirements



Product parameters
Inspiratory resistance(30LPM±1LPM):≤7MMH2O
Inspiratory resistance(95LPM±1LPM):≤24MMH2O
Filtration efficiency(salt spray 1%):≥94%
Filtration efficiency(paraffin oil or DOP 1%):≥94%
Headband tension:20N/10s

### Product features

- CE FFP2 CERTIFIED: FFP2 masks remove at least 94% of non -oil-based particles down to 0.3 microns.
- COMFORTABLE & ADJUSTABLE: High quality, light weight construction provides comfort, while the adjustable nose clip with foam and heavy duty straps conforms to your facial features for an enhanced seal.
- DISPOSABLE: Compactly designed to go anywhere, these single-use, all -in-one FFP2 face masks are an economical choice for respiratory protection.
- Common Uses: Prevents particulate matter from the processing of minerals, coal, iron ore, flour, etc.



waste  
reducing  
product life



Scan to  
learn about  
protecting planet  
information

### Ningbo Fastest Safety Protection Products Co.,Ltd.

Rm. 1801 Jiamei Buliding, No.746 Taikang Zhong Rd., Yinzhou District, Ningbo China, 315199  
TEL: +86-574-82822581 FAX: +86-574-82822578 EMAIL: ft@ftsafety.cn  
Website: www.ftsafety.com