

FT2307V-FFP2

Respirator



The masks offer half-face coverage with 2 headband style straps for a secure fit. The cupped design offers low breathing resistance and is ergonomically designed for comfort.

Descriptions
MATERIALOF BODY PART
4 Ply Nonwoven
Outer layer: 100g PP
Middle layer: 25g double layers melt blown fabric
Inner layer: 30-40g PP
MATERIAL OF NOSE CLIP
Adjustable AluminumBraided
MATERIAL OF HEAD ON STRIP
Spandex elastic
SPONGE BAR
Polyurethane (PU) foam
SIZE
One size
BREARHING VALVE DEVICE
Yes
PRODUCTION METHOD
Ultrasonic welded
REUSABLE
No
STYLE
Foldable mask with Valve

PACKAGE
15 PCS/BOX
240PCS/CTN
Carton dimension: 64*31.5*43.5CM
Net weight: 3.5KG
Gross weight:5.6KG



Certification
Safety masks meettheEuropean standardEN149:2001+A1:2009 FFP2 standard requirements



Product parameters
Inspiratory resistance(30LPM±1LPM):≤7MMH2O
Inspiratory resistance(95LPM±1LPM):≤24MMH2O
Filtration efficiency(salt spray 1%):≥94%
Filtration efficiency(paraffin oil or DOP 1%):≥94%
Headband tension:20N/10s

Product features

- CE FFP2 CERTIFIED: FFP2 masks remove at least 94% of non -oil-based particles down to 0.3 microns.
- COMFORTABLE & ADJUSTABLE:High quality, light weight construction provides comfort, while the adjustable nose clip with foam and heavy duty straps conforms to your facial features for an enhanced seal.
- BREATHE EASY:Built-in exhalation cool valve reduces heat, moisture, and humidity build-up, to keep you more comfortable longer
- Common Uses:Prevents particulate matter from the processing of minerals, coal, iron ore, flour, etc.



waste
reducing
product life



Scan to
learn about
protecting planet
information

Ningbo Fastest Safety Protection Products Co.,Ltd.

Rm. 1801 Jiamei Buliding, No.746 Taikang Zhong Rd., Yinzhou District,Ningbo China,31 5199
TEL: +86-574-82822581 FAX: +86-574-82822578 EMAIL: ft@ftsafety.cn
Website: www.ftsafety.com